

# WEL-7500 Euro Handle Lock

## Main Features

- Ability to adjust Daylight Saving Time
- Ability to update (read/write) to the card
- Transponder: Mifare Classic (13.56Mhz)
- Max Users: 64,000
- Max Doors: 64,000
- Time zones: 200, each time zone consists of 12 periods
- 128 calendars
- Opening mode:
  1. Standard (default 6 seconds)
  2. Toggle
  3. Timed Toggle
  4. Office Hour Mode
- Emergency Open / Emergency Close mode programmed via a card
- Initial setup by System Programmer thereafter updated by card
- Smart sleep mode
- Acoustic Low Power Warning
- Emergency Power Pack available in case of flat batteries
- Transponder reading distance: up to 20mm
- Totally wire free
- Easy to retrofit onto existing mortise lock cases
- Firmware can be upgraded by FDMS
- Lock opening time adjustable by card update
- Managed by e-Link network system software
- 1024 events stored in the memory

## Technical Specification

- Escutcheon size: 290mm (H) x 40mm (W) x 20.5mm (D)
- Battery life: standby 3 years or 50,000 operations
- Battery spec: 3 x AAA 1.5V
- Environment:
  - IP54 (Recommended for internal installation only)
  - Operating Temperature -20°C to 70°C
- EN1634-1 E1 60 Fire Resistant
- Available with Euro Profile cylinder cut-out
- Axis distance from handle centre to cylinder: 72mm, 85mm, 92mm
- Suitable for door thickness: 38 -50 mm as standard
- Standard finish SSS (other finishes available by request)

