

e-Link Wall Readers

WR-1500 Standard Wall Reader (Internal Application)

Main Features

- Compact design
- Transponder: Mifare Classic (13.56Mhz)
- Reading distance: up to 40mm
- LED indication
- Updates & validates cards
- Event reading from cards
- Acoustic indication of card acceptance
- Firmware can be upgraded by FDMS

Technical Specification

- Pre-wired with 3 metres of cable to controller (Optional: 10 metres)
- Power: from WR-2500 controller
- Current draw: 100mA
- Environment:
IP55 (Recommended for internal installation only)
Operating Temperature -20°C to 70°C
- Reader dimension: 115mm x 32mm x 13mm
- Surface mount only
- Communication through RS485 to controller

WR-1520 IP67 Rated Wall Reader (External or Internal Application)

Main Features

- Metal Frame
- Supplied with a separate mounting plate for ease of install
- Transponder: Mifare Classic (13.56Mhz)
- Reading distance: up to 25mm
- LED indication
- Updates & validates cards
- Event reading from cards
- Acoustic indication of card acceptance
- Firmware can be upgraded by FDMS

Technical Specification

- Pre-wired with 3 metres of cable to controller (Optional: 10 metres)
- Power: from WR-2500 controller
- Current draw: 100mA
- Environment:
IP67
Operating Temperature -20°C to 70°C
- Reader dimension: 90mm x 90mm x 13mm
- Surface fix or mount on a standard UK flush back box
- Communication through RS485 to controller

